



ACCESSORIES • Mastics & Nails



Mastics

Your Benefits:

- IKO mastics allow you to work in strong wind areas, on slopes greater than 60° and in colder weather conditions
- IKO mastics are all 100 % compatible with IKO shingles
- Completely impermeable to water
- Excellent adhesion to bituminous materials
- Superb adhesion to concrete
- Easy application
- Resistant to diluted acids and alkalis

Nails

Your Benefits:

- Top quality nails allow durable shingle installation at minimal cost
- IKO nails do not rust or damage shingles

Mastics & Nails



ACCESSORIES • Mastics & Nails

• Shingle Stick®





Premium Elastomeric bitumen based mastic

• Plastal Stick® and Plastal®





Elastomeric bitumen based mastic

• Nails

are hot galvanised extra large head professional steel wire roofing nails.

	Shingle Stick®	Plastal Stick®	Plastal®
			
Colour	Black		
Density at 20°C	± 1,2 kg/l	± 1,3 kg/l	± 1,3 kg/l
Drying time – RH 50–60 % – touch dry	± 24 h		
Flash point	41° C		
Temperature resistance	from – 20 to 80 °C		
Application	from 0 to 40 °C		
Packaging	310 ml (12 pc./box)	310 ml (12 pc./box)	5 kg
	 <p style="text-align: center;">** 60° - 85°</p>		

For more details on how and when to use mastic, see our application guide

	IKO Galvanised nails		BOSTITCH coiled nails	
				
Diameter shaft	± 3,0 mm	± 3,0 mm	3,05 mm	
Diameter head	≥ 9,0 mm	≥ 9,0 mm	10,1 mm	
Zinc coating	7,5 microns (± 30 %)	7,5 microns (± 30 %)	8 microns	
Packaging	1 kg	5 kg		
Length	20 mm	± 690 pcs. / ± 20 m ²	± 3450 pcs. / ± 98 m ²	-
	25 mm	± 582 pcs. / ± 16 m ²	± 2910 pcs. / ± 83 m ²	7200 pcs. / ± 205 m ²
	30 mm	-	± 2480 pcs. / ± 70 m ²	-
	31 mm	-	-	7200 pcs. / ± 205 m ²
	35 mm	-	± 2150 pcs. / ± 61 m ²	-
				

For more details on how and when to use nails, see our application guide